

Autobag® PS 125™ Tabletop Baggers – The Ultimate in Hand Load Packaging Systems

The Autobag® PS 125™ and PS 125 OneStep™ Tabletop Baggers are specifically designed to bring simplicity, versatility, quality and value to hand load packaging applications.

Operating at speeds up to 25 bags per minute (15 BPM OneStep version), the PS 125 bagging systems offer innovative engineering in a simple, tabletop design. The PS 125 features a small footprint of 560 x 480 mm, and weighs just 37kg. The quiet, all-electric design does not require compressed air to run, making the unit highly adaptable in any low- to mid-volume production environment.

The PS 125 is simple to operate, with a user-friendly display that enables easy access to operating parameters, job set-up, job storage, and on-board system diagnostics. The unique, locking turntable combines with the AutoThread™ feature to provide ergonomic handling and changeover of Autobag bags-on-a-roll. Bags are automatically indexed, loaded by hand, then sealed using the Push-to-Seal™ function, a standard footswitch, or via automatic cycle control.

The PS 125 OneStep™ includes the same conveniences of the standard PS 125 with the addition of a built-in PH 412 printer. Featuring next-bag-out printing technology that is ideal for short run and order fulfilment applications, the PS 125 OneStep is capable of printing high resolution graphics, text and barcodes directly on the bag, eliminating the need for a separate labeling operation. The printer features a tilt-back print head for easy maintenance, and the optional AutoLabel™ design software simplifies label creation.

Using system-matched Autobag pre-opened bags-on-a-roll in sizes up to 260 mm wide and 430 mm long, the PS 125 and PS 125 OneStep offer a simple, and cost effective packaging solution.



Next-bag-out printing feature ensures greater accuracy and eliminates product queuing in order fulfilment applications*




Stores jobs for later recall using operator-friendly controls



Markets Served

- Aerospace & Defense
- Automotive
- Electronics
- Food
- Hardware & Fasteners
- Healthcare
- Hobby & Craft
- Household Products
- Mail Order Fulfilment
- Cosmetics
- Pet Products
- Plumbing Parts




Open load area and controlled seal bar maximise loading flexibility and operator safety



Locking turntable and AutoThread™ feature provide easy bag access and changeover

*PS 125 OneStep version only

Features and Benefits

All Electric System

Compressed air is not required to operate

Operator-Friendly

Easy to navigate menu with job storage and recall, as well as on-board diagnostics to maximise productivity and uptime

Print Capabilities

Prints high resolution graphics, text and barcodes directly on the bag*; tilt-back printer head for easy maintenance

Compact

Compact design is ideal for low- to mid-volume packaging operations

Film Control

Dancer assembly for positive bag-web control provides accurate positioning for inline printing*, loading and sealing




Bag Support

Multi-position bag support shelf for flexibility



Easy Maintenance

Tilt-back printer* enables fast and easy maintenance and is system-matched for highest print quality using genuine AutoLabel™ Thermal Transfer Ribbon



System Matched Bags



Service & Support



Custom Engineering & Integration

Optional Additions

- Bag Deflators
- Simple Funnels
- AutoLabel™ Designer Software*

Technical Information

PS 125



↳ 480 mm Length x 560 mm Width ↳

PS 125 OneStep



↳ 480 mm Length x 560 mm Width ↳

PS 125	
Weight	37 kg
Electrical	110/220 VAC; 50/60 Hz; 5.0/2.7 Amps
Pass-Through	Up to 86 mm
Bag Thickness	35 to 100µm
Bag Sizes	W 55 to 260 mm L 102 to 430 mm

PS 125 OneStep	
Weight	50 kg
Electrical	110/220 VAC; 50/60 Hz; 5.0/2.7 Amps
Pass-Through	Up to 86 mm
Bag Thickness	35 to 100µm
Bag Sizes	W 55 to 260 mm L 102 to 430 mm

*PS 125 OneStep version only

📞 01681 891 400 ✉️ mktonline@autobag.co.uk 🌐 autobag.co.uk

🏠 Automated Packaging Systems Ltd, Enigma Business Park, Sandys Road, Malvern, WR14 1JJ

© Mar 2017 Automated Packaging Systems. Features, Options & Technical Specifications subject to change. The use of the © or ™ symbol indicates that Automated Packaging Systems, Inc. has registered or is otherwise claiming trademark rights in the United States. These marks may also be registered in other countries and common law rights may apply in countries where such rights are recognized. 3/17 7.5M

 **Automated**
PACKAGING SYSTEMS